

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



(19)

(11) Publication number: **08132034 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **06302934**(51) Intl. Cl.: **C02F 1/40 B01D 21/24**(22) Application date: **11.11.94**

(30) Priority:

(43) Date of application
publication: **28.05.96**(84) Designated contracting
states:(71) Applicant: **HITACHI KIDEN KOGYO LTD**(72) Inventor: **YOSHIDA TERUHISA
GOTO MASAHIRO**

(74) Representative:

**(54) DISCHARGE METHOD
OF SCUM**

(57) Abstract:

PURPOSE: To provide a discharge method of scum by which the scum floating on a water surface can be efficiently discharged and staying and growth of the scum on the whole surface of a water surface of a sedimentation tank is restrained, in the sedimentation tank having a circular or rectangle water surface and being provided with a feed well in the center.

CONSTITUTION: In the sedimentation tank 1 having the feed well 3 in the center, plural set of float type scum skimmers 5 provided in the radiation direction centering around the feed well 3 are successively operated and then the scum floating in the vicinity of the float type scum skimmers 5 is successively collected. Thus, the scum floating over the whole surface of the water surface of the tank is surely discharged outside the tank.

COPYRIGHT: (C)1996,JPO

